



145 - 160 WP

+ 0/+5 WP Positive Tolerance

ROOFTOP AND OFF-GRID DESIGN

✓ HIGH QUALITY

25 year linear performance
5 year product warranty



GENERAL CHARACTERISTICS

Cell	Polychrystalline solar cell 156.75 x 156.75 mm
No. of Cells(connections)	36(4x9)
Panel Dimensions	1480 x 680 x 30 mm
Weight	11 kg
Connectors and cable	IP65, 3 bypass diodes 0.9 m cables

POLY SERIES 145-160WP



ELECTRIC PERFORMANCE at STC*

	145 Wp	150 Wp	155 Wp	160 Wp
Maximum Power	145 Wp	150 Wp	155 Wp	160 Wp
Power Tolerance	0/+5 Wp	0/+5 Wp	0/+5 Wp	0/+5 Wp
Maximum Power Voltage	18 V	18 V	18 V	18.98 V
Maximum Power Current	8.05 A	8.16 A	8.34 A	8.43 A
Open Circuit Voltage	22.6 V	22.8 V	22.8 V	22.87 V
Short Circuit Current	8.72 A	8.94 A	9.2 A	8.99 A

*Standard Test Conditions: 1000W/m² irradiance, 25°C and AM = 1.5

HIGH PERFORMANCE

25 25 years linear performance

5 5 years product warranty



THERMAL CONDITIONS

Normal Operating Cell Temperature 800W/m ² Irradiance, 20°C, AM = 1.5	48C ±2°C
Power Temperature Coefficient	-0.5%/K
Current Temperature Coefficient	0.035%/K
Voltage Temperature Coefficient	-0.37 MV/K



Solar Panels for Recreation and Small-Scale Installations.
Wacomp Business CC Reg no 2001 / 032052 / 23

10 Grenache Close, Zevenzicht Estate
Langverwacht Rd, Kuils River, 7580

Ph: 087 700 4819 // 082 500 1204
E-mail: info@solarflex.co.za